No. 120

21607302000

PT.	MARKER	GRID BEARING	GRID DIST.	GROUND DIST.	STATE PLANE COORDINATES		DESCRIPTION
1	P.K. NAIL	S 89°39'00"W	35.362'	35.36'	670,738.145 N	1,638,764.396 E	P.K. NAIL 34.65' WEST OF CENTER OF MANHOLE AT INTERSECTION.
2	IRON PIPE	N 50°06'36"E	46.038'	46.04'	670,767.886 N	1,638,835.081 E	EX. BLOCK CORNER BURIED AT BACK OF SIDEWALKS.
3	BOLT	N 80°58'17"E	176.194'	176.21'	670,766.011 N	1,638,973.768 E	EX. BOLT.
4	NAIL	N 86°17'53"E	237.350'	237.37'	670,753.686 N	1,639,036.612 E	SET A NAIL IN TOP OF CURB FOR A GPS POINT.

N.W.-CORNER
SECTION 29-16-7.
1½" IRON PIPE.

N 00°31'54"E, 2652.13'
(GRID)

AVENUE

30'

ST. ANDREWS STREET

60'

18.5'

30'

103.04'

COMPUTED POINT FOR
THE W. 1/4-COR., 29-16-7
FALLS ON THIS MANHOLE.
670,738.361 N
1,638,799.757 E

N 00°42'06"E, 2638.86'
(GRID)

COPELAND

BUILDING CORNER.

BUILDING

149.7' NORTH OF
CHISELED "X" OF RECORD.
"X" IS OFFSET 1' WEST.

35'

35'

N

GRID NORTH

SCALE: 1" = 20'

0 5 10 15 20 30 40

GRID FACTOR: 0.9999267

S.W.-CORNER
SECTION 29-16-7.
3½" ALUMINUM CAP.

Ⓜ : COMPUTED LOCATION ONLY. THE LOCATION OF THE W. 1/4-COR., SEC. 29-16-7 FALLS ON A MANHOLE COVER AT A VERY BUSY STREET INTERSECTION. THE CORNER LOCATION FALLS AT THE INTERSECTION OF THE CENTERLINES WHICH THE RECORDS INDICATE WAS THE OLD 1/4-CORNER POSITION.

I, WILLIAM C. JUNG, COUNTY SURVEYOR
HEREBY CERTIFY THAT THE CORNER LOCATION SHOWN ON THIS RECORD WAS DETERMINED BY ME OR UNDER MY DIRECTION AND CONTROL AND THAT THIS U.S. PUBLIC LAND SURVEY MONUMENT RECORD IS CORRECT AND COMPLETE TO THE BEST OF MY KNOWLEDGE AND BELIEF.

William C. Jung 11/26/03
SIGNATURE DATE

WISCONSIN
WILLIAM C. JUNG
S-1323
ONALASKA, WIS.
LAND SURVEYOR

DRAFTED BY: P.F. FOLLANSBEE - LA CROSSE COUNTY SURVEYOR'S DEPARTMENT. 8/01/2003

TIE SHEET: W. 1/4-COR., SEC. 29-16-7.

COMPUTED POINT THAT FALLS ON A MANHOLE. Ⓜ	670,738.361 N	1,638,799.757 E

No. 120
21607302000