SET A DRILL HOLE IN THE CONCRETE GUTTER ON THE EAST SIDE OF "LANG DRIVE". 0.40' EAST OF GUTTER LIP AND 1.62' WEST OF THE FLOW-LINE. 63.72' NORTH OF THE N.W.-COR. OF THE EDGE OF IRON OF THE OUTER FRAME HOLDING A STORM GRATE.

C. 1/4-COR., 32-16-7.
665,409.803 N
1,641,429.259 E

ALLEY

ALLEY

S.W.-COR., 32-16-7.
EXIST. IRON BAR.
662,764.912 N
1,638,863.101 E

N 01°22'31" W, 2668.45'

AVENUE

STREET

S.E.-COR., 32-16-7.
EXIST. P.K. NAIL.
662,717.443 N
1,644,134.179 E

N 89°30'13" W, 2630.30'

S 89°27'53" E, 2640.99'

MAIN

STREET

COMPUTED POINT FOR THE S.1/4-COR., 32-16-7.
NOTHING SET.
662,742.12 N
1,641,493.30 E

SURVEY POINT ONLY.

ALLEY

WEST

13 th

N

GRID NORTH

SCALE: 1" = 40'

0 10 20 30 40 60 80

GRID FACTOR: 0.9999267

PT.	MARKER	STATE PLANE COORDINATES	
1	P.K. NAIL	662,705.594 N	1,641,118.101 E
2	IRON BAR	662,783.970 N	1,641,275.399 E
3	IRON BAR	662,782.723 N	1,641,395.974 E
4	P.K. NAIL	662,942.639 N	1,641,448.842 E
5	D.O.T. POINT	662,696.905 N	1,641,444.381 E
6	IRON PIPE	662,701.014 N	1,641,813.224 E
7	2" IRON PIPE	662,698.796 N	1,641,821.474 E

COMPUTED LOCATION ONLY. THE LOCATION OF THE S.1/4-COR., SEC. 32-16-7 FALLS AT A VERY BUSY STREET INTERSECTION. THE CORNER LOCATION FALLS AT THE INTERSECTION OF THE CENTERLINES WHICH THE RECORDS INDICATE WAS THE OLD 1/4-CORNER POSITION.

I, WILLIAM C. JUNG, COUNTY SURVEYOR
HEREBY CERTIFY THAT THE CORNER LOCATION SHOWN ON THIS RECORD WAS DETERMINED BY ME OR UNDER MY DIRECTION AND CONTROL AND THAT THIS U.S. PUBLIC LAND SURVEY MONUMENT RECORD IS CORRECT AND COMPLETE TO THE BEST OF MY KNOWLEDGE AND BELIEF.

William C. Jung — 4/6/05
SIGNATURE — DATE

WISCONSIN
WILLIAM C. JUNG
S-1323
ONALASKA, WIS.
LAND SURVEYOR

TIE SHEET: S. 1/4-COR., SEC. 32-16-7.

COMPUTED POINT: NOTHING SET. 662,742.12 N | 1,641,493.30 E

DRAFTED BY: P.F. FOLLANSBEE - LA CROSSE COUNTY SURVEYOR'S DEPARTMENT. 4/05/2005.

CL-3078

16-7-32-4
City of La Crosse